



2001 Antique Gold



2001 Antique Gold



7001 Leather



7003 Sundown


Features

El Paso is a 3/8" x 7" ply-core engineered Hickory floor with a unique surface texture unlike any other product in our Shaw Hardwood Collection. El Paso showcases a rustic distressing that features circular saw marks randomly peppered throughout the product. The timeworn look and texture mimics the appearance aged reclaimed flooring, but in a wider width than commonly found in true reclaimed flooring.


Specifications

Style	SA469
Thickness	3/8" (10mm)
Width	7"
Species	Hickory
Texture	Distressed
Gloss Level	20%
Janka Hardness Rating	1820
Edge Description	Microbeveled
End Description	Microbeveled
Sq. Ft. per Carton	28.60
Sq. Ft. per Pallet	858.00

Trim Pieces *when ordering please include color number*




SRH38
Flush Reducer



SORH8
Overlap Reducer



SSH38
Flush Stairnose



SOSH8
Overlap Stairnose



SCH38
Threshold / Carpet Reducer



TMH78
T-Molding



QTR96
Quarter Round



This Shaw hardwood is warranted that the finish of this product will not peel off or wear through for 50 years from the date of purchase.



This Shaw hardwood is approved for installation over water type radiant heated subfloors. Floating installation method only. Direct glue-down is NOT recommended!



This hardwood is rated High color and character variation with distinguishable color variation within each box. It is *imperative* that hardwood planks from various cartons be continually blended during installation to insure optimum appearance.



This Shaw hardwood meets the GREENGUARD indoor air quality requirements and is GREENGUARD Certified.



This Shaw hardwood is Cradle to CradleSM Silver Certified.



This Shaw product can be installed above, on or below ground level.

Suggested Adhesive

- HS091 - Shaw 4-in-1 Urethane Adhesive - Slab moisture up to 85% RH / 12 lbs
- HS097 - Shaw 3-in-1 MS Adhesive - Slab moisture up to 90% RH / 15 lbs
- HS105 - Shaw 35MC Urethane Adhesive - Slab moisture up to 90% RH / 15 lbs
- SWADH - Shaw UreBond Plus Urethane Adhesive - Slab moisture up to 80% RH / 8 lbs
- HS090 - Shaw EcoMade Resin Adhesive - Slab moisture up to 75%RH / 3 lbs
- HS096 - Shaw 70 Adhesive Resin Adhesive - Slab moisture up to 75%RH / 3 lbs
- TNGAD - Shaw Tongue and Groove Adhesive - Formulated for floating installations