

RIVERSTONE

engineered





RIVERSTONE



Style Number	SW593	
Construction	EPIC Plus	
Thickness	Nominal 3/8"	
Width	6¾"	
Species	Hickory	
Texture	Heavy Scraped	
Gloss Level	20%	
Janka Hardness Rating	2059	
Edge Description	Pillowed	
End Description	Pillowed	
SF per carton	30.48	
SF per pallet	1,371.60	
Installation	Nail, Staple, Glue, Float	Cartons may include random lengths

Features

- Scraped hickory in a low gloss color palette that ranges from cool to warm
- The chattered and scraped surface accentuates the naturally wide range of character found in the hickory hardwood species
- High variation in color, scrape and texture should be expected from plank to plank

Suggested Recommendations

Style #	Riverstone	Coverage	Moisture	Additional Features		
ADHESIVES						
HS105	35MC — Urethane	35 SF / gal for moisture	No Moisture test required	Sound & crack suppressant		
		60 SF / gal as adhesive	Up to 5 lbs. or 85% RH			
111SA	3-in-1 Ultra - MS	35 SF per gal. for moisture	No Moisture test required	Sound & crack suppressant		
		70 SF per gal. as adhesive	Up to 5 lbs. or 85% RH			
HS304	DMC140 — Urethane	35 SF / gal for moisture	No Moisture test required			
SWADH	UreBond Plus	35 SF / gal for moisture	Up to 8 lbs. or 85% RH			
		60 SF / gal	Up to 5 lbs. or 85% RH			

Trim Pieces length: 78" (*Overlap Reducer and Overlap Stairnose are designed for floating installations only. These items are non-stocking — but are available through a quick-ship program. Delivery should take approximately 2 to 3 weeks.)



SRH38 Flush Reducer



SROH8*Overlap
Reducer



SSH38 Flush Stairnose



SOSH8*Overlap
Stairnose



SCH38 Threshold | Carpet Reducer



TMH78 T-Molding



QTR96 Quarter Round

Benefits



















