



2009 Caramel



5011 Charcoal



7009 Cider



7017 Cocoa



5011 Charcoal

Essex Maple

Specification

*Cartons may include random lengths

Style	SA464
Thickness	3/8"
Width	5"
Species	Maple
Texture	Distressed
Gloss Level	20%
Janka Hardness Rating	2039
Edge Description	Pillowed
End Description	Pillowed
Sq. ft. per carton	19.72
Sq. ft. per pallet	1,143.00

Features

The inspiration for Essex Maple originated from the aged and distressed wood we see in vintage floors. The rich undertone creates harmony and balance between the natural movement of rustic maple wood grain and the subtleties of authentic age and character. This timeless visual tapestry will compliment any interior design style.

Style	Adhesive	Coverage	Moisture Control	Other
SWADH	UreBond Plus	60 sq. ft./gal	Up to 5 lbs or 85% RH	Most popular
HS105	35MC	60 sq. ft./gal as adhesive	Up to 5 lbs or 85% RH	Sound control & crack suppressant
		35 sq. ft./gal for moisture	Yes, no limit	
HS304	DMC 140	35 sq. ft./gal for moisture	Yes, no limit	

*We recommend that you use Shaw's adhesives to prolong the life, durability and performance of your beautiful new EPIC Plus hardwood floor.



This Shaw EPIC+ hardwood is warranted that the finish will not peel off or wear through for as long as you own your home.



This product features ScufResist™ PLATINUM - Shaw's extremely wear resistant UV cured polyurethane finish with Aluminum Oxide designed to help resist household scuffing on hardwood floors.



Stabilitek core is built for high performance and lasting durability. Constructed from wood fibers bonded with proprietary chemistry, Stabilitek holds up to the challenges of climate fluctuation and sub floor moisture.



This hardwood is rated High color and character variation with distinguishable color variation within each box. It is imperative that hardwood planks from various cartons be continually blended during installation to ensure optimum appearance.



This Shaw hardwood is approved for installation over water type radiant heated subfloors. Floating installation method only. Direct glue-down is NOT recommended!



This Shaw hardwood is Cradle to Cradle™ Silver Certified.



This Shaw product can be installed above, on or below ground level.



Made in the U.S.A.




PRODUCT CERTIFIED FOR LOW CHEMICAL EMISSIONS
UL.COM/GG
UL2818

Trim Pieces when ordering please include color number



SRH38
Flush
Reducer



SORH8
Overlap
Reducer



SSH38
Flush
Stairnose



SOSH8
Overlap
Stairnose



SCH38
Threshold /
Carpet Reducer



TMH78
T-Molding



QTR96
Quarter
Round