

# **ALBRIGHT OAK**

engineered







## **ALBRIGHT OAK**



Style Number	SW581	SW582	
Construction	Epic Plus	Epic Plus	
Thickness	Nominal 3/8"	Nominal 3/8"	
Width	31/4"	5"	
Species	Red Oak	Red Oak	
Texture	Smooth	Smooth	
Gloss Level	20%	20%	
Janka Hardness Rating	1889	1889	
Edge Description	Microbeveled	Microbeveled	
End Description	Microbeveled	Microbeveled	
SF per carton	23.76	23.66	
SF per pallet	1,425.60	1,419.60	
Installation	Nail, Staple, Glue, Float	Nail, Staple, Glue, Float	
All measurements are nominal	Cartons may include random lengths		

### **Features**

- Classic hardwood flooring in both traditional and modern colors.
- Showcases the charm and natural beauty of hardwood, accentuated with a wide range of character.

#### **Suggested Adhesive**

Style Name	Coverage	Moisture	Additional Features	
ADHESIVES				
35MC — Urethane	35 SF / gal for moisture	No Moisture test required	Sound & crack suppressant	
	60 SF / gal as adhesive	Up to 5 lbs. or 85% RH		
3-in-1 Ultra - MS	35 SF per gal. for moisture	No Moisture test required	Sound & crack suppressant	
	70 SF per gal. as adhesive	Up to 5 lbs. or 85% RH		
DMC140 — Urethane	35 SF / gal for moisture	No Moisture test required		
UreBond Plus	35 SF / gal for moisture	Up to 8 lbs. or 85% RH		
	60 SF / gal	Up to 5 lbs. or 85% RH		
	35MC — Urethane  3-in-1 Ultra - MS  DMC140 — Urethane	WES  35MC — Urethane 35 SF / gal for moisture 60 SF / gal as adhesive  3-in-1 Ultra - MS 35 SF per gal. for moisture 70 SF per gal. as adhesive  DMC140 — 35 SF / gal for moisture Urethane  UreBond Plus 35 SF / gal for moisture	VES  35MC — Urethane 35 SF / gal for moisture No Moisture test required 60 SF / gal as adhesive Up to 5 lbs. or 85% RH  3-in-1 Ultra - MS 35 SF per gal. for moisture No Moisture test required 70 SF per gal. as adhesive Up to 5 lbs. or 85% RH  DMC140 — 35 SF / gal for moisture No Moisture test required Urethane UreBond Plus 35 SF / gal for moisture Up to 8 lbs. or 85% RH	

We recommend that you use Shaw's adhesives to prolong the life, durability and performance of your beautiful new EPIC floor.

**Trim Pieces** length: 78" (\*Overlap Reducer and Overlap Stairnose are designed for floating installations only. These items are non-stocking — but are available through a quick-ship program. Delivery should take approximately 2 to 3 weeks.)



**SFR18**Flush
Reducer



\*Overlap Reducer



SFS18 Flush Stairnose



\$\$018 \*Overlap Stairnose



SCR18 Threshold / Carpet Reducer



**SWTM8** T-Molding



SQTR8 Quarter Round

#### **Benefits**



















