



Each board in this collection is sanded, painted white and then individually sanded by hand to allow the natural beauty and character of the wood to peak through the paint along some edges and where embellishments occur naturally in the wood. This sand-through creates dramatic variation that is further enhanced by a final top stain that completes the look.

Style Number	AA775
Construction	Engineered
Thickness	1/2"
Width	5"
Species	Red Oak
Texture	Smooth/Handsanded
Gloss Level	20%
Janka Hardness Rating	1610
Edge Description	Beveled
End Description	Beveled
SF per carton	26.01
SF per pallet	1014.39
Installation	Nail, Staple, Glue, Float

All measurements are nominal Cartons may include random lengths


Sundry Recommendations

Style #	Style Name	Coverage	Moisture Test	Additional Features
ADHESIVES				
A35MC	35MC – Urethane	35 SF / gal for moisture 60 SF / gal as adhesive	No Moisture test required Up to 5 lbs. or 85% RH	Sound control & crack suppressant
AA807	3-in-1 Ultra – MS	35 SF / gal for moisture 70 SF / gal as adhesive	No Moisture test required Up to 5 lbs. or 85% RH	Sound control & crack suppressant
AA772	DMC140 – Urethane	35 SF / gal for moisture	No Moisture test required	
AA856	UreBond Plus	35 SF / gal for moisture 60 SF / gal	Up to 8 lbs. or 85% RH Up to 5 lbs. or 85% RH	

Trim Pieces length: 78" (*Overlap Reducer and Overlap Stairnose are designed for floating installations only. These items are non-stocking – but are available through a quick-ship program. Delivery should take approximately 2 to 3 weeks.)



AFR12
Flush Reducer



AAOL1
*Overlap Reducer



AFS12
Flush Stairnose



AAOS1
*Overlap Stairnose



ATH12
Threshold | Carpet Reducer



AATMD
T-Molding



AAQTR
Quarter Round

Benefits

