

## Mackenzie Maple shawbuilderflooring.com





## Features

Mackenzie Maple offers stunning style. Combining maple's softly subtle grain with heavy scraping creates a look that's high in character and visually cool. 3/8" thick and 5" wide, the planks have pillowed edges and ends. Just the floor for relaxed family living.

Also availabe in  $3^{1}/4^{"}$ ,  $5^{"}$ ,  $6^{3}/8^{"}$  mixed width:

HW549 Mackenzie Maple



## **Specifications**

Style	HW547
Thickness	3/8" (9.5mm)
Width	5″
Species	Maple
Texture	Heavy Scraped
Gloss Level	20%
Janka Hardness Rating	2039
Edge Description	Pillowed
End Description	Pillowed
Sq. ft. per carton	HW547 <b>19.72</b>
	SW548 <b>25.40</b>
Sa ft nor nallet	HW5471183 20

Sq. ft. p

. per carton	HW547 <b>19.7</b>
	SW548 <b>25.4</b> 0
. per pallet	HW547 1183.20

SW548 1143.00

Cartons may contain random length planks



Scuf<sub>Resist</sub>

This Shaw Duras hardwood is warranted that the finish will not peel off or wear through for 50 years.

This Shaw hardwood is approved for RADIANT HEAT

installation over water type radiant heated subfloors. Floating installation method only. Direct glue-down is NOT recommended!

This product features ScufResist™ PLATINUM - Shaw's extremely wear resistant UV cured polyurethane finish with Aluminum Oxide designed to help resist household scuffing on hardwood floors.



This hardwood is rated High color and character variation with distinguishable color variation within each box. It is imperative that hardwood planks from various cartons be continually blended during installation to insure optimum appearance.

This Shaw hardwood meets the GREENGUARD indoor air quality requirements and is GREENGUARD Certified.



This Shaw hardwood is Cradle to Cradle<sup>CM</sup> Silver Certified.



This Shaw product can be installed above, on or below ground level.

lade ir

Made in the U.S.A.

## Trim Pieces when ordering please include color number





HRH38 Flush Reducer

HROH8 **Overlap Reducer** 



HCH38 Threshold / Carpet Reducer



HWTMH T-Molding



HSH38 HSOH8 Flush Stairnose Overlap Stairnose



**HWQR0** Quarter Round

Suggested Adhesive

- HS303 Shaw DMC140 (premium urethane adhesive) No moisture testing required
- HWA05 Shaw 35MC Urethane Adhesive Moisture and Sound Control - No moisture testing required.
- HWADH Shaw Urebond Plus Adhesive Slab moisture up to 80% RH / 8 lbs
- BTGAD Shaw Tongue and Groove Adhesive Formulated for floating installations