

## **GRANT GROVE**

engineered





## **GRANT GROVE**



| <b>Construction</b> Epic        | Plus                  | Epic Plus                 | Finin Divin   |  |
|---------------------------------|-----------------------|---------------------------|---|--|
|                                 | II (O O)              | •                         | Epic Plus   |  |
| Thickness 3/8'                  | " (8.2mm)             | 3/8" (8.2mm)              | 3/8" (8.2mm)  |  |
| Width 5"                        |                       | 63/8"                     | $3\frac{1}{4}$ ", 5, $6\frac{3}{8}$ " mixed - packaged together |  |
| <b>Species</b> Hick             | kory                  | Hickory                   | Hickory   |  |
| <b>Texture</b> Scra             | aped                  | Scraped                   | Scraped   |  |
| Gloss Level 20%                 | ó                     | 20%                       | 20%   |  |
| Janka Hardness Rating 258       | 4                     | 2584                      | 2584  |  |
| Edge Description Pillo          | owed                  | Pillowed                  | Pillowed  |  |
| End Description Pillo           | owed                  | Pillowed                  | Pillowed  |  |
| SF per carton 23.6              | 66                    | 30.48                     | 34.69   |  |
| SF per pallet 1,419             | 9.60                  | 1,371.60                  | 1,561.05  |  |
| <b>Installation</b> Nail        | , Staple, Glue, Float | Nail, Staple, Glue, Float | Nail, Staple, Glue, Float                                       |  |
| Installation Grade Abo          | ove, On               | Above, On                 | Above, On   |  |
| Color Variation High            | h                     | High                      | High  |  |
| Radiant Heat Approved Yes       |                       | Yes                       | Yes   |  |
| <b>GREENGUARD Certified</b> Yes |                       | Yes                       | Yes   |  |
| Warranty Life                   | time                  | Lifetime                  | Lifetime  |  |

All measurements are nominal. Cartons may include random lengths

## **Sundry Recommendations**

| Style #   | Style Name        | Coverage                 | <b>Moisture Test</b>      | <b>Additional Features</b>        |  |  |
|-----------|-------------------|--------------------------|---------------------------|-----------------------------------|--|--|
| ADHESIVES |                   |                          |                           |                                   |  |  |
| HS105     | 35MC — Urethane   | 35 SF / gal for moisture | No moisture test required | Sound control & crack suppressant |  |  |
|           |                   | 60 SF / gal as adhesive  | Up to 5 lbs. or 85% RH    |                                   |  |  |
| 111SA     | 3-in-1 Ultra — MS | 35 SF / gal for moisture | No moisture test required | Sound control & crack suppressant |  |  |
|           |                   | 70 SF / gal as adhesive  | Up to 5 lbs. or 85% RH    |                                   |  |  |
| SWADH     | UreBond Plus      | 35 SF / gal for moisture | Up to 8 lbs. or 85% RH    |                                   |  |  |
|           |                   | 60 SF / gal              | Up to 5 lbs. or 85% RH    |                                   |  |  |

**Trim Pieces** – Length: 78" (\*Overlap Reducer and Overlap Stairnose are designed for floating installations only. These items are non-stocking — but are available through a quick-ship program. Delivery should take approximately 2 to 3 weeks.)





