



100 Bianco



500 Driftwood



600 Natural



700 Saddle

Style Number	CS32L	CS58V
Construction	ceramic	ceramic
Tile Type	floor tile	floor tile
Tile Size	6" x 24"	6" x 36"

Technical

Wear Rating Group	3	3
Break Strength	305 lbs	305 lbs
Water Absorption	4%	4%
DCOF	> 0.54	> 0.54
Shade Variation	V2	V2

A DCOF value of > 0.42 is the new standard for tiles specified for commercial application in standard A137.1-2012, Section 9.6. It replaces the SCOF value of > 0.60 referenced in ASTM C1028. For more information on the correlation between the two values and about the DCOF AcuTest visit the Tile Council of North America's website: www.tcnatile.com

MANUFACTURER'S WARNING:

- Tiles with DCOF Acutest values less than .42 are not recommended for use in areas with wet or slippery conditions. If such tiles are used as a walking surface where water, ice, oil, great and/or other substances are present, such a condition could cause a reduction in foot traction and become unexpectedly slippery resulting in a fall and personal injury. See ANSI standard A137.1 section 6.2.2.1.10, available at www.tcnatile.com/sections6.2.2.1.10.html.
- Water, oil, grease, etc. create slippery conditions. Floor applications with exposure to these conditions require extra caution in product selection. Not for use on ramps.
- For additional information, refer to [Factors to Consider](#).
- Since there is a shade variation on all natural products, the tile and trim supplied for your particular installation may not match these samples. Final selection should be made from actual tiles and trim and not from tile and trim samples or color reproductions. Manufactured in accordance with ANSI A137.1 standards.

Colors We recommend that this product be installed with no less than a 3/16" grout joint.



100 Bianco



500 Driftwood



600 Natural



700 Saddle

Benefits

