

MACKENZIE MAPLE II

engineered











Style Number	HW604	HW605	HW618		
Construction	DURAS	DURAS	DURAS		
Thickness	3/8" (8.2mm)	3/8" (8.2mm)	3/8" (8.2mm)		
Width	5"	63/8"	$3\frac{1}{4}$ ", 5", $6\frac{3}{8}$ " mixed - packaged together		
Species	Maple	Maple	Maple		
Texture	Heavy Scraped	Heavy Scraped	Heavy Scraped		
Gloss Level	20%	20%	20%		
Janka Hardness Rating	2233	2233	2233		
Edge Description	Pillowed	Pillowed	Pillowed		
End Description	Pillowed	Pillowed	Pillowed		
SF per carton	23.66	30.48	34.69		
SF per pallet	1,419.60	1,371.60	1,561.05		
Installation	Nail, Staple, Glue, Float	Nail, Staple, Glue, Float	Nail, Staple, Glue, Float		
All measurements are nominal Cartons may include random lengths					

Features

- · Combines maple's softly subtle wood grain with heavy scraping to create a relaxed setting
- Available in single widths (5" or $6\frac{3}{8}$ ") or mixed width option

Sundry Recommendations

Style #	Style Name	Coverage	Moisture Test	Additional Features		
ADHESIVES						
HWA05	35MC — Urethane	35 SF / gal for moisture	No Moisture test required	Sound control & crack suppressant		
		60 SF / gal as adhesive	Up to 5 lbs. or 85% RH			
111BA	3-in-1 Ultra — MS	35 SF / gal for moisture	No Moisture test required	Sound control & crack suppressant		
		70 SF / gal as adhesive	Up to 5 lbs. or 85% RH			
HS303	DMC140 — Urethane	35 SF / gal for moisture	No Moisture test required			
HWADH	UreBond Plus	35 SF / gal for moisture	Up to 8 lbs. or 85% RH			
		60 SF / gal	Up to 5 lbs. or 85% RH			

Trim Pieces length: 78" (*Overlap Reducer and Overlap Stairnose are designed for floating installations only. These items are non-stocking — but are available through a quick-ship program. **Delivery should take approximately 2 to 3 weeks.**)







HSH38 I Flush * Stairnose S



HSOH8*Overlap
Stairnose

*Carpet



HCH38 Threshold | Carpet Reducer



HWTMH T-Molding



HWQRO Quarter Round

Benefits



















