# TILE & STONE

### **ELEGANCE** ceramic wall tile | porcelain accents

### CS64P | Basketweave



CS63P | Pinwheel



190 White w/ Black Dot

CS61P | Hexagon




CS62P | 2" x 2" with Dot



# TILE & STONE

Hexagon Mosaic Matte Finish 10" x 12" sheet CS61P





100 White

190 White w/ Black

2" x 2" Dot Mosaic Matte Finish 12" x 12" sheet CS62P





100 White

190 White w/ Black

Pinwheel Mosaic Matte Finish 12" x 12" sheet CS63P



190 White w/ Black

Basketweave Mosaic Matte Finish 12" x 12" sheet CS64P



190 White w/ Black

### **Benefits**







# TILE & STONE

### CS68P | Beveled Diamond



CS65P | Penny Round



500 Warm Grey



CS66P | Mini Brick

CS67P | Lantern



500 Warm Grey



# TILE & STONE

Mini Brick Mosaic
Gloss Finish
11" x 12" sheet
CS66P








Penny Round Mosaic

Gloss Finish

12" x 12" sheet

CS65P



100 White



101 Biscuit



Lantern Mosaic Gloss Finish 10" x 11.5" sheet CS67P








500 Warm Grey

500 Warm Grey

Diamond Mosaic

Gloss Finish







500 Warm Grey

**Benefits** 





# TILE & STONE

## **ELEGANCE**

ceramic wall tile | porcelain accents





Style Number (Bullnose	<del>)</del> )			CS35L	CS85M
Construction				ceramic	ceramic
Tile Type				bullnose	bullnose
Tile Size				3" x 6"	4" x 16"
<b>3" x 6"</b> Gloss Finish					
CS34L	100 White	101 Biscuit	200 Linen	500 Warm Grey	550 Taupe
4" x 16" Gloss Finish CS36L	100 White	101 Biscuit	200 Linen	500 Warm Grey	550 Taupe
2" x 2" Mosaic Gloss Finish 12" x 12" x 2" CS37L	100 White	101 Biscuit	200 Linen	500 Warm Grey	550 Taupe

A DCOF value of > 0.42 is the new standard for tiles specified for commercial application in standard A137.1-2012, Section 9.6. It replaces the SCOF value of > 0.60 referenced in ASTM C1028. For more information on the correlation between the two values and about the DCOF AcuTest visit the Tile Council of North America's website: www.tcnatile.com

#### MANUFACTURER'S WARNING:

- Tiles with DCOF Acutest values less than .42 are not recommended for use in areas with wet or slippery conditions. If such tiles are used as a walking surface where water, ice, oil, great and/or other substances are present, such a condition could cause a reduction in foot traction and become unexpectedly slippery resulting in a fall and personal injury. See ANSI standard A137.1 section 6.2.2.1.10, available at www.tcnatile.com/sections6.2.2.1.10.html.
- Water, oil, grease, etc. create slippery conditions. Floor applications with exposure to these conditions require extra caution in product selection. Not for use on ramps.
- For additional information, refer to Factors to Consider.
- Since there is a shade variation on all natural products, the tile and trim supplied for your particular installation may not match these samples. Final selection should be made from actual tiles and trim and not from tile and trim samples or color reproductions. Manufactured in accordance with ANSI A137.1 standards.

The basis of a beautiful kitchen! This collection starts with the classic 3" x 6" wall tile and adds an exciting new size and shape - 4" x 16" - for an elegant, modern look. Mosaics and coordinating bullnose round out the series.

- Wall Tile
  - Porcelain with glossy finish
  - Perfect for kitchen backsplashes and shower walls
- Matte Mosaics
  - Porcelain: Suitable for floors and walls

- Gloss Mosaics
   Porcelain: Suitable for walls
  - Bullnose
    - Porcelain with glossy finish

CS35L BULLNOSE MUST BE USED WITH 3" x 6" WALL TILE

CS85M bullnose must be used with  $4" \times 16"$  wall tile

#### **Benefits**



