



 **Shaw**
Tile & Stone™

Como | *porcelain tile*

Colors shown 220 Beige

shawfloors.com



Como

Features

Featuring a blend consistent with the visual of premium grade cross cut and vein cut travertine, "Como" truly defines the look of elegance for the traditional living space; coolly sophisticated for the contemporary!

- Clarity Digital Imaging for a highly realistic, rich visual
- Wide assortment of sizes: 12x12, 18x18, 12x24, 24x24, and mosaics
- 3 versatile colors Almond, Beige, and Noce



Colors



100 Almond



220 Beige



750 Noce

Accents

MOSAIC



100 Almond



220 Beige



750 Noce

Tile Sizes

Field Tile	Style
24x24	CS29K
12x24	CS28K
13x13	CS26K
18x18	CS27K

Trim	Style
3" x 13" Bullnose	CS30K

Accent	Style
2" x 2" Mosaic	CS31K

Technical	
Wear Rating Group	4
Break Strength	420 lbs.
Water Absorption	.5%
COF (Wet)	.6

This tile features random variations of shade and texture within each carton. To insure optimum appearance, it is imperative that tiles from various cartons be continually blended during installation. Placement of tiles should be decided on before beginning installation.

*OSHA (Occupational Safety and Health Administration) has established a recognized industry standard of 0.5 (wet and dry) for slip-resistant surfaces. The Americans with Disabilities Act (ADA) recommends, but does not require, "a Static Coefficient of Friction of 0.60 for accessible routes and 0.80 for ramps." ADA does not specifically state that 0.60 is both a dry and a wet requirement. It is important to note that any tile or other hard surface flooring can become slippery when wet or improperly maintained. Products installed in an exterior application must comply with applicable ANSI 108 series of the "American National Standard Specifications for the Installation of Ceramic Tile" and comply with TCA installation methods applicable to installation conditions.



Approved Usage

