



Color shown on floor is 701

 **Shaw** Tile & Stone™
shawfloors.com

Sicily | *porcelain tile*



Tile & Stone™

shawfloors.com

Shaw Industries, Inc.

PO Drawer 2128, Mail Drop 02601

Dalton, GA 30722-2128

1-800-441-7429

Sicily

Features

- This distinctive color-body porcelain tile offers a rustic stone visual that will enhance any floor, wall or counter top installation
- Rustic appearance
- Superior stain and fade resistance
- Natural stone colorations
- Frost resistant

Accents



100



500



700



701



Multi Border 101

Tile Sizes

Field Tile	Style
13" x 13"	CS730
18" x 18"	CS731
6.5" x 6.5"	CS732

Trim

3" x 13" Bullnose	CS739
V-Cap	CS740
V-Cap Corner	CS741
Quart Round	CS742
Quart Round Beak	CS743

Accent

13" x 13" Mosaic	CS734
4" x 12" Multi Border 101	CS48D

Technical

Wear Rating Group	5
Break Strength	295 lbs.
Water Absorption	.5%
COF (Wet)	.61

This tile features random variations of shade and texture within each carton.

To insure optimum appearance, it is imperative that tiles from various cartons be continually blended during installation. Placement of tiles should be decided on before beginning installation.

*OSHA (Occupational Safety and Health Administration) has established a recognized industry standard of 0.5 (wet and dry) for slip-resistant surfaces. The Americans with Disabilities Act (ADA) recommends, but does not require, "a Static Coefficient of Friction of 0.60 for accessible routes and 0.80 for ramps." ADA does not specifically state that 0.60 is both a dry and a wet requirement. It is important to note that any tile or other hard surface flooring can become slippery when wet or improperly maintained. Products installed in an exterior application must comply with applicable ANSI 108 series of the "American National Standard Specifications for the Installation of Ceramic Tile" and comply with TCA installation methods applicable to installation conditions.

Approved Usage

