






Color shown is 405 Thistle




39212 Breeman




39372 Albany




39405 Thistle



39522 Hampshire



650 Estate



976 Antler

Features

Logan's Point's engineered 5" planks feature an elegant time-worn subtle scraped finish. Offered in three rich colors, the pronounced graining in this hickory species creates a floor that is rustic yet refined.

- Premium "oak or harder" veneer core for improved impact resistance and structural stability
- Unsurpassed richness with multi-step staining process
- Unsurpassed visual with premium core construction at an unbelievable value
- Premium American Hickory species
- Made right here in the USA by Shaw

Trim Pieces when ordering please include color number



HAR38
Flush Reducer



HAS38
Flush Stairnose



HATH8
Threshold / Carpet
Reducer



HATMD
T-Molding



HAQTR
Quarter Round

Suggested Adhesive

- HWA91 – Shaw 4-in-1 Urethane Adhesive – Slab moisture up to 85% RH / 12 lbs
- HWA97 – Shaw 3-in-1 MS Adhesive – Slab moisture up to 90% RH / 15 lbs
- HWA05 – Shaw 35MC Urethane Adhesive – Slab moisture up to 90% RH / 15 lbs
- HWADH – Shaw UreBond Plus Urethane Adhesive – Slab moisture up to 80% RH / 8 lbs
- HWA90 – Shaw EcoMade Resin Adhesive – Slab moisture up to 75%RH / 3 lbs
- HWA96 – Shaw 70 Adhesive Resin Adhesive – Slab moisture up to 75%RH / 3 lbs
- BTGAD – Shaw Tongue and Groove Adhesive – Formulated for floating installations

Specifications

Style	HW441
Thickness	3/8" (8.5mm)
Width	5"
Species	Hickory
Texture	Subtle Scraped
Gloss Level	20%
Janka Hardness Rating	1926
Edge Description	Beveled
End Description	Beveled
Sq. Ft. per Carton	34.69
Sq. Ft. per Pallet	1,352.91

**Cartons may include random lengths*



This Shaw hardwood is warranted that the finish of this product will not peel off or wear through for 50 years from the date of purchase.



This product features ScufResist™ PLATINUM – Shaw's extremely wear resistant UV cured polyurethane finish with Aluminum Oxide designed to help resist household scuffing on hardwood floors.



This Shaw hardwood is approved for installation over water type radiant heated subfloors. Floating installation method only. Direct glue-down is NOT recommended!



This hardwood is rated High color and character variation with distinguishable color variation within each box. It is **imperative** that hardwood planks from various cartons be continually blended during installation to insure optimum appearance.



This Shaw hardwood is Cradle to Cradle™ Silver Certified.



This Shaw product can be installed above, on or below ground level.



This Shaw product is Made in the U.S.A.



This Shaw hardwood meets the GREENGUARD indoor air quality requirements and is GREENGUARD Certified.