

KINGS CANYON II engineered





shawbuilderflooring.com 02.16.2018

KINGS CANYON II



Style Number	HW622	HW601	
Construction	DURAS	DURAS	
Thickness	3/8" (8.2mm)	3/8" (8.2mm)	
Width	5″	6 ³ / ₈ ″	
Species	Hickory	Hickory	
Texture	Wire Brushed	Wire Brushed	
Gloss Level	20%	20%	
Janka Hardness Rating	2584	2584	
Edge Description	Pillowed	Pillowed	
End Description	Pillowed	Pillowed	
SF per carton	23.66	30.48	
SF per pallet	1,419.60	1,371.60	
Installation	Nail, Staple, Glue, Float	Nail, Staple, Glue, Float	
All measurements are nominal	Cartons may include random lengths		

Features

- Offering just a touch of texture without producing the aggresive, rugged results of scraped hardwood floors
- Pillowed edges and ends give each plank a pronounced sculpted appearance
- Texture will range from light to extreme

Sundry Recommendations

Sunary Recommendations					
Style #	Style Name	Coverage	Moisture Test	Additional Features	
ADHESIVES					
HWA05	35MC — Urethane	35 SF / gal for moisture	No Moisture test required	Sound control & crack suppressant	
		60 SF / gal as adhesive	Up to 5 lbs. or 85% RH		
111BA	3-in-1 Ultra — MS	35 SF / gal for moisture	No Moisture test required	Sound control & crack suppressant	
		70 SF / gal as adhesive	Up to 5 lbs. or 85% RH		
HS303	DMC140 — Urethane	35 SF / gal for moisture	No Moisture test required		
HWADH	UreBond Plus	35 SF / gal for moisture	Up to 8 lbs. or 85% RH		
		60 SF / gal	Up to 5 lbs. or 85% RH		

Trim Pieces length: 78" (*Overlap Reducer and Overlap Stairnose are designed for floating installations only. These items are non-stocking — but are available through a quick-ship program. **Delivery should take approximately 2 to 3 weeks**.)



Builder Flooring

